

Touch Mobile Computer

# EF501R



## The One Device that Does All

### • Ultimate Performance

A powerful octa-core processor ensures higher level of performance that can run multiple applications with minimum power consumption. Running Android 7.0 Nougat, the EF501R provides ultimate on-the-go productivity packed with enterprise-focused features.

### • Enterprise Durability

Bluebird's most rugged 5-inch touch mobile computer for use outdoors and in harsh industrial environments. Perfectly combines premium enterprise class mobility and rugged industrial design.

### • All-Day Power

High-capacity, user replaceable battery delivers the longest working hours and with Hot-Swap mode, users can change the battery without having to reboot, keeps the device in full service.

### • Exceptional Connectivity

Whether indoors or in the field, EF501R provides the fastest, reliable wireless connections with support for the fastest Wi-Fi and 4G LTE, enabling workers to stay connected from anywhere.

### • The Most Advanced Scanning

With the advanced scanning technology, workers can capture 1D and 2D barcodes as well as dirty and damaged barcodes quickly and accurately.



### Industries

- Retail
- Field Services
- Healthcare
- Transportation & Logistics
- Warehouse Management

### Use Cases

- Customer Engagement
- Merchandising & Inventory Checks
- Competitive Pricing
- Staff Collaboration & Communication
- Order Taking

## EF501R Specification

|   |   |   |
|---|---|---|
| <b>PERFORMANCE CHARACTERISTICS</b>                | CPU   | 2.0 GHz Octa Core Processor   |
|   | Operating System  | Android 7.X   |
|   | Memory  | 2GB RAM / 16GB Flash (Default), 4GB RAM / 32GB Flash (Optional)   |
| <b>PHYSICAL CHARACTERISTICS</b>                   | Dimensions (L x W x D)  | 166.5 x 88.75 x 28.9 mm   |
|   | Weight  | 360g  |
|   | Display   | 5.0 inch. HD (1280 x 720)   |
|   | Imager Window   | Corning Gorilla Glass 3   |
|   | Touchpanel  | Capacitive multi-touch Glove, Wet, Stylus   |
|   | Backlight   | LED backlight   |
|   | NIT   | 330 Nit, 500 NIT (Optional)   |
|   | Power   | User replaceable Battery, Standard: 3.8V, 6400 mAh  |
|   | Hot swap  | Support   |
|   | Quick charging  | 3.8 hours, Standard battery with charging cradle  |
|   | Expansion Slot  | MicroSD 32GB SDHC, up to 128GB SDXC   |
|   | SIM / SAM   | 2 Micro SIM / 1 SAM   |
|   | Interface   | 1 x USB Typc C (3.0)Docking Connector (USB 2.0)   |
|   | Notification  | Audible tone; multi-color LEDs; vibration   |
|   | Keypad  | On-screen keypad  |
|   | Voice and Audio   | Dual noise-cancelling microphones; High-quality speaker phone; 3.5mm headset jack   |
| PTT Hot Key                                       | Support   |   |
| <b>WIRELESS WAN DATA AND VOICE COMMUNICATIONS</b> | Radio Frequency Band  | (Optional)<br>Korea<br>- LTE : 850, 2100, 2600 (FDD 5,1,7)<br>Americas<br>- LTE : 850/1700/1800/1900/2100/2600 (FDD 5,4,3,2,1,7)<br>Worldwide<br>- LTE : 800, 850, 900, 1800, 2100, 2600 (FDD 20,5,6,8,9,3,1,7)<br>- UMTS/HSPA/HSPA+: 850/900/1800/2100 (FDD 5,8,3,1)<br>- GSM/GPRS/EDGE: 850/900/1800/1900 |
|   | GPS   | A-GPS, GLONASS, BEIDOU (Default)A-GPS, GLONASS, Galileo (Optional)  |
| <b>WIRELESS LAN</b>                               | Radio   | 802.11 a/b/g/n/d/h/i/r/ac   |
|   | Data Rates  | 5GHz: 802.11a/n/ac – up to 500 Mbps;2.4GHz: 802.11b/g/n – up to 144Mbps   |
|   | Security and Encryption   | WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA/WPA2 Enterprise (TKIP and AES)<br>– EAPTTLS (PAP, MSCHAP, MSCHAPv2),EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC, EAP Fast3 and LEAP  |
| <b>WIRELESS PAN</b>                               | Bluetooth   | Bluetooth 4.2 LE , Class 1  |
| <b>WIRED LAN</b>                                  | Ethernet  | Support (w/ Ethernet Cradle)  |
| <b>COMMUNICATION AND MESSAGING</b>                |   | VoIP / PTT  |
| <b>DATA CAPTURE</b>                               | Scanning  | 1D&2D imager  |
|   | Camera  | Rear : 13MP Autofocus with flash, Front : 2.0MP Fixed Focus   |
|   | NFC   | (Optional)ISO 14443 Type A and B; F; FeliCa, and ISO 15693 cards, MiFare  |
|   | Biometrics  | Support (Optional)  |
| <b>PAYMENT</b>                                    | MSR   | Support (Optional)  |
|   | Contact   | Support (Optional)  |
| <b>SENSOR</b>                                     | Light Sensor  | Ambient Light   |
|   | Motion Sensor   | Proximity, Gyroscope, Accelerometer, Magnetic   |
| <b>USER ENVIRONMENT</b>                           | Operating Temp.   | -20°C to 60°C / -4°F to 140°F   |
|   | Storage Temp.   | -40°C to 70°C / -40°F to 158°F  |
|   | Humidity  | 95% non-condensing  |
|   | Drop Spec.  | 2.4m / 8 ft. to concrete at room temp. per MIL-STD 810G   |
|   | Tumble Spec.  | 2,000 3.2ft./1.0 m tumbles; meets and exceeds IEC tumble specifications   |
|   | Sealing   | IP67  |
|   | Vibration   | 4 g's PK Sine (5 Hz to 2 kHz); 0.04g2/Hz Random (20 Hz to 2 kHz); 60 minute duration per axis, 3 axis   |
|   | Thermal Shock   | -40° C to 70° C rapid transition  |
| Electrostatic Discharge (ESD)                     | +/-15kVdc air discharge+/-8kVdc direct discharge+/-8kVdc indirect discharge |   |

### Accessories



Bluebird Inc.  
(Corporate Headquarters)

SEI Tower 13-14F, 39 Eonju-ro 30-gil, Gangnam-gu, Seoul, Korea. Postal#06292 / Phone. +82.1577.0778 Fax. +82.2.6499.2242

Copyright © 1995-2017 Bluebird Inc. All rights reserved. Bluebird Inc. is the designer and manufacturer of Bluebird handheld mobiles. Bluebird logo is registered trademark of Bluebird Inc.

[www.bluebirdcorp.com](http://www.bluebirdcorp.com)