



DESKTOP BARCODE

LABEL PRINTER

LK-B20

- Thermal transfer and direct thermal printing
- Stable & reliable label printing
- High speed 152mm per second
- High capacity memory
- Large capacity of roll (200mm OD) with external media holder
- Less ribbon replacement with 360M length (Wax, Resin, Wax/Resin)
- Paper width adjustable from 18mm to 118mm
- Selectable optional Auto cutter or Peeler





INTERFACE



◀ LK-B20 INTERFACE

Standard interface card

- USB
- Parallel(IEEE-1284)

Optional interface card

- Serial(RS-232C), Ethernet,
- Wi-Fi 802.11b

PEELER



AUTO CUTTER



● SPECIFICATION

ITEM	TYPE	
MODEL	LK-B20(LK-B21)	
PRINT METHOD	Thermal Transfer and Direct Thermal	
PRINTING SPEED	152 mm/sec	
PRINT WIDTH	104mm(4.1")	
PRINT LENGTH	1250mm(49.2")	
RESOLUTION	203 DPI(8 dots/mm)	
PAPER WIDTH (min~max)	18mm ~ 118mm(0.7" ~ 4.25")	
PAPER ROLL SIZE (min~max)	Internal	Ø 25.4(1")~ Ø 127mm(5.0")
	External	Ø 38.1(1.5")~ Ø 200mm(7.8")
PAPER THICKNESS	0.06 ~ 0.20mm	
PAPER TYPE	Label, Tag, Continuous, Fanfold	
PAPER SENSOR	Label Gap Sensor, Black Mark Sensor, Notch Sensor	
RIBBON WIDTH	33mm ~110mm(1.3 ~ 4.3")	
RIBBON LENGTH	360M, Ø 67mm(2.5")	
MEMORY	STANDTAD	8MB SDRAM, 5MB Flash
	OPTION	16MB Flash
BARCODE	1D	Code39, Code128 with subsets A/B/C, UCC/EAN-128, Code 93, Codabar, Interleaved 2 of 5, UPC-A , UPC-E, UPC-A and UPC-E with 2 or 5 digit extensions, Postnet, Plessey, German Post Code, MSI-3
	2D	MaxiCode, PDF417, Datamatrix, QR Code, Code 49
FONT SPECIFICATION	6 bitmapped – 8x12, 10x16, 12x20, 14x24, 32x48, 24x24(KSC5601)	
	7 bitmapped-5x9, 7x11, 10x18, 15x28, 13x26, 40x60, 13x21	
	1 Smooth Scalable	
PROGRAMMING LANGUAGE	EPLII, ZPLII Command compatible	
POWER	AC100~240V, 24VDC, 2.92A	
DIMENSIONS	215mm x 287mm x 231mm	
WEIGHT(kg)	3.6kg	



BARCODE



PAPER SENSOR



EASY LOAD



COMPACT DESIGN



HIGH SPEED



PEELER



VARIOUS INTERFACE



PAPER WIDTH



A/T



DIRECT OR TRANSFER



SEWOO TECH Co., Ltd.

374-2, Gajang-dong, Osan-si, Gyeonggi-do, 447-210, Korea

T. +82-31-459-8200 F. +82-31-459-8880

www.miniprinter.com